

MODEL ZW209BP - Pressure Reducing Valve with Low Flow By-Pass Control Valve Order Form



Customer: _____ Date: _____

Contact: _____ Email: _____

Telephone/Fax: _____ Ref. P. O. _____

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Size: ☐ 1-1/4" (DN32) ☐ 1-1/2" (DN40) ☐ 2" (DN50) ☐ 2-1/2" (DN65) ☐ 3" (DN80) ☐ 4" (DN100) ☐ 6" (DN150)

Function Options:

- Check all that apply
- ☐ "C" Option * - Check Valve with Isolation Valve
 - ☐ "L" Option * - Closing Speed Control
 - ☐ "O" Option * - Opening Speed Control (Standard on 4" or smaller)

Valve body is ductile iron, epoxy coated

Body Options:

- Check one
- ☐ Standard - Full Port Globe Body
 - ☐ "A" Option - Angle Style Body
 - ☐ "R" Option - Reduced Port Body (3" (DN80) - 6" (DN150) Flanged Only)



End Connections (Check one)

Size Range (1-1/2" - 6", DN40 - DN150)

- | Options | Description |
|-----------------------------------|--|
| ☐ Standard | - ANSI Class 150 Flanges |
| ☐ BSD | - BS10/AS2129 Table D Flanges |
| ☐ BSE | - BS10/AS2129 Table E Flanges |
| ☐ BSF * | - BS10/AS2129 Table F Flanges |
| ☐ BSH * | - BS10/AS2129 Table H Flanges |
| ☐ "G" | - IPS Grooved, ANSI/AWWA C 606 |
| ☐ "BG" | - Grooved 2-1/2" (76.1 mm pipe OD) |
| ☐ "Y"* | - ANSI Class 300 Flanges (1-1/2" - 4", DN40 - DN100) |

- | Options | Description |
|---------------------------------|--------------------------|
| ☐ PN6 | - ISO Class PN6 Flanges |
| ☐ PN10 | - ISO Class PN10 Flanges |
| ☐ PN16 | - ISO Class PN16 Flanges |
| ☐ PN25 * | - ISO Class PN25 Flanges |

Size Range (1-1/4" - 3", DN32 - DN80)

- ☐ "TH" - NPT Threaded, ANSI/ASME B1.20.1
- ☐ "BS" - Threaded British Pipe Parallel BSPP/G size ISO
- ☐ "BT" - Threaded British Pipe Tapered BSPT/Rc size ISO

Main Valve Options:

- Check all that apply
- ☒ Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
 - ☐ "V" Option * - Viton Rubber Internals, Rated 180°F (only available with "LP" or "HP" options)
 - ☐ "Z" Option * - Visual Position Indicator

Pilot Options:

- Check one
- ☒ Standard - Isolation Valves, Inlet and Outlet Pressure Gauges, and "Wye" Type Strainer
-
- Check one
- ☐ Standard - PRXL Pilot (15 - 150 psi)
 - ☐ "LP" Option * - PV-PRD Pilot (5 - 25 psi)
 - ☐ "HP" Option * - PV-PRD Pilot (30 - 300 psi)
-
- Check all that apply
- ☐ Standard - Copper Tubing and Brass Fittings
 - ☐ "ST" Option * - Stainless Steel Tubing ("included with SP option, only replaces Copper Tubing")
 - ☐ "SP" Option * - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing. "GL" Option included)
 - ☐ "SH" Option * - Stainless Steel Braided Hoses (only replaces Copper Tubing)
-
- Check all that apply
- ☐ "RV" Option - Pilot Installed on Reverse Side
 - ☐ "GL" Option * - Liquid Filled Pressure Gauge

*Adder to standard price applies

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurnwilkins.com
or visit us online at www.zurn.com

