

MODEL ZW209 - Pressure Reducing Valve Control Valve Order Form



Customer: _____ Date: _____

Contact: _____ Email: _____

Telephone/Fax: _____ Ref. P. O. _____

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Size: ☐ 1-1/4" (DN32) ☐ 1-1/2" (DN40) ☐ 2" (DN50) ☐ 2-1/2" (DN65) ☐ 3" (DN80) ☐ 4" (DN100)
Check ☐ 6" (DN150) ☐ 8" (DN200) ☐ 10" (DN250) ☐ 12" (DN300) ☐ 14" (DN350) ☐ 16" (DN400)
one

Function Options:

Check ☐ "C" Option * - Check Valve with Isolation Valve
all that ☐ "L" Option * - Closing Speed Control
apply ☐ "O" Option * - Opening Speed Control (Standard on 4" or smaller)


Valve body is ductile iron, epoxy coated

Body Options:

Check ☐ Standard - Full Port Globe Body
one ☐ "A" Option - Angle Style Body (1-1/4" (DN32) - 10" (DN250)
☐ "R" Option - Reduced Port Body (3" (DN80) - 10" (DN250) Flanged Only)

End Connections (Check one) Size Range (1-1/2" - 16", DN40 - DN400)

Options	Description	Options	Description
☐ Standard	- ANSI Class 150 Flanges	☐ "PN6"	- ISO Class PN6 Flanges
☐ "BSD"	- BS10/AS2129 Table D Flanges	☐ "PN10"	- ISO Class PN10 Flanges
☐ "BSE"	- BS10/AS2129 Table E Flanges	☐ "PN16"	- ISO Class PN16 Flanges
☐ "BSF"*	- BS10/AS2129 Table F Flanges	☐ "PN25"*	- ISO Class PN25 Flanges
☐ "BSH"*	- BS10/AS2129 Table H Flanges		
☐ "G"	- IPS Grooved, ANSI/AWWA C 606		
☐ "BG"	- Grooved 2-1/2", or 6" (76.1 mm or 165.1mm pipe OD)		
☐ "Y"*	- ANSI Class 300 Flanges		



Main Valve Options:

Check ☒ Standard - Stainless Steel Seat, Seal Ring Retainer and Stem Guide
all that ☐ "V" Option * - Viton Rubber Internals, Rated 180°F, 82°C (1-1/4" - 6", DN32 - DN150 only available with
apply ☐ "Z" Option * - Visual Position Indicator

Pilot Options:

Check ☒ Standard - Isolation Valves, Inlet and Outlet Pressure Gauges, and "Wye" Type Strainer

Check ☐ Standard - PRXL Pilot (15 - 150 psi, 100 - 1000kPa)
one ☐ "LP" Option * - PV-PRD Pilot (5 - 25 psi, 35 - 170kPa)
☐ "HP" Option * - PV-PRD Pilot (30 - 300 psi, 205 - 2050kPa)

Check ☐ Standard - Copper Tubing and Brass Fittings
all that ☐ "ST" Option * - Stainless Steel Tubing ("included with SP option, only replaces Copper Tubing")
apply ☐ "SP" Option * - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve and Copper Tubing.
"GL" Option included)
☐ "SH" Option * - Stainless Steel Braided Hoses (only replaces Copper Tubing)

Check ☐ "RV" Option - Pilot Installed on Reverse Side
all that ☐ "GL" Option * - Liquid Filled Pressure Gauge
apply

*Adder to standard price applies

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurn.com
or visit us online at www.zurn.com

