

SA-38 NEO Angle Shower Alcove Wall

SHOWER ALCOVE WALLS


WARRANTY

Limited Lifetime – Residential

Limited 5-year – Commercial

Manufactured from Veritek®

(See page 2 for detailed information.)



SA-38 NEO

Designed to fit wall areas 38" deep x 38" wide* x 72" high (965 mm x 965 mm x 1829 mm)

FEATURES

- Nails directly to studs for fast installation.
- Sturdy interlocking system for one-piece appearance.
- Panels easily fit through existing doorways and can be installed by one person.
- Made of Veritek® composite material with no surface coating to chip or crack.
- The SA-38 NEO is a three piece compression-molded unit with a natural gloss surface.

SPECIFICATIONS

SA-38 NEO Veritek® Angle Shower Alcove Wall

		Wall Area	Ship	Ship	Carton	
Model	Part	Designed To Fit	Wt. Lb.	FedEx	Dims. In.	Cu. Ft.
SA-38 NEO	NEoooooSA	38" D x 38" W* x 72" H (965 mm x 965 mm x 18		-	76 x 36 x 13	20.58
Fits NEO shower floor size 38" D x 38" W (965 mm x 965 mm)						

^{*1-1/2-}inch additional area required on outer edges of wall panels to accommodate nail-up flange.

Kit Includes: One right side panel, one left side panel, one corner panel, wall mounting clips and installation instructions.

Packaging: Each kit is packed in a flat, rectangular carton.

COLORS

(See inside back cover for color sample.)

Solid Colors:

Aggregate Colors:

- White (010)
- Bermuda Sand (040)
- Bone (037)
- Gray Granite (042)
- Bisque (018)
- Tahiti Desert (050)
- Bright White (137)
- Pearl (138)

MAINTENANCE AND CLEANING INFORMATION

Clean regularly with common household liquid cleaners and a sponge or soft cloth. For hard water stains, scale removers can be used. To protect finish, fiberglass wax or automotive paste wax can be applied. **Do not** use abrasive cleaners or scouring pads. **Do not** use "leave on" cleaning products, such as automatic spray shower cleaners. Prolonged contact with harsh chemicals could have an adverse reaction over time and discolor surfaces. **Do not** use cleaning agents that caution use on acrylic, polyester or plastics.

SUPPORT DOCUMENTS

Installation instructions available at swanstone.com.

